


Product Name	<p align="center">Portable Lighting Line 50m (Model: 4BDL-0500) (Classification number: 46161793, Identification number: 23099702)</p>																		
Product Specifications	<p>◦ A portable light-emitting evacuation guide lighting line that can mark an escape route so that you can evacuate quickly and accurately in thick smoke and darkness</p> <p>【Specifications】</p> <ul style="list-style-type: none"> ◦ Size (Dimension): H(200) × W(240) × D(110) ◦ Weight (Including Removable Battery): 2.9 ± 0.2kg ◦ Lighting Line Length: 50m ± 0.5m ◦ Lighting Line Diameter: 3.0mm ± 0.3mm ◦ Flame Retardant: UL94-V0 ◦ Brightness: luminance 30 cd/m² and more ◦ Light-emitting line: High Carbon Steel Wire inserted with tensile strength 2,200N/mm² and more ◦ IP code: Light-emitting line – IPx8 / Main body – IP55 ◦ Portability: Single Operation ◦ Power: 12V 2.6A ~ 3.0A (Removable and Rechargeable external battery used) ◦ Operating Time <p align="right">(Unit: Minutes)</p> <table border="1" data-bbox="264 875 1307 1155"> <tr> <td>Operating mode</td> <td>Hi</td> <td>Mid</td> <td>Low</td> </tr> <tr> <td>Lighting on</td> <td>170</td> <td>186</td> <td>220</td> </tr> <tr> <td>Flashing (1 blink per second)</td> <td>338</td> <td>380</td> <td>465</td> </tr> <tr> <td>Visual alarm (3 blinks per second)</td> <td>365</td> <td>445</td> <td>555</td> </tr> </table> <ul style="list-style-type: none"> ◦ Battery level indicator function (LED – Max, Mid, Min) ◦ Brightness control function (3 Levels – High, Mid, Low) <p>【Key Functions】</p> <ul style="list-style-type: none"> ◦ Two-way signal communication system type <ul style="list-style-type: none"> – Reciprocal transmission and reception of lighting, flashing, and visual alarm signals between the main body and the emergency button <p>【Product photo】</p> <div style="text-align: center;">  </div> <ul style="list-style-type: none"> ◦ Components: Main body, Charging adapter, Battery 2ea, Shoulder strap, Name tag, Product user manual 			Operating mode	Hi	Mid	Low	Lighting on	170	186	220	Flashing (1 blink per second)	338	380	465	Visual alarm (3 blinks per second)	365	445	555
Operating mode	Hi	Mid	Low																
Lighting on	170	186	220																
Flashing (1 blink per second)	338	380	465																
Visual alarm (3 blinks per second)	365	445	555																
Remarks	<ul style="list-style-type: none"> – Warranty: 2 durable years of free repair (except for EL Wire & Battery) – Performance Certification (Ministry of SMEs and Startups (MSS), Designation of excellent products (Public Procurement Service), 12th Firefighting Industry Technology Award Winner – Submission of certificates and certified test reports (17 cases) upon delivery (※ Certified test items: 17 test other than spare power(Battery) test) – Patent registered (10-1689150), Design Patent registered (30-0908622), Korea, USA and Japanese patent registered 																		