


Product Name	<p align="center">Lighting Line(Underwater) 25m (Model : 4BDL-0251) (Classification number: 46161793, Identification number: 23024246)</p>													
Purpose	<ul style="list-style-type: none"> ◦ A personal underwater light-emitting evacuation guide lighting line that can mark an escape route so that you can evacuate quickly and accurately for underwater rescue and search activities 													
Product Specifications	<p>【Specifications】</p> <ul style="list-style-type: none"> ◦ Size (Dimension): H(200) × W(138) × D(93) ◦ Weight: 1.3 kg ± 0.3 kg ◦ Lighting Line Length: 25m ± 0.5m / Diameter: 3.0mm ± 0.3mm ◦ Flame Retardant: UL94-V0 ◦ Brightness: luminance 30 cd/m² and more ◦ Light-emitting line: High Carbon Steel Wire inserted with tensile strength 2,200N/mm² and more ◦ Waterproof: Depth of water – 50m ◦ Portability: Single Operation ◦ Power: Rechargeable Lithium-ion battery – 7.2V, 5.2A ◦ Operating Time 													
	(Unit: Minutes)													
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Operating mode</th> <th style="width: 20%;">Lighting on</th> <th style="width: 20%;">Flashing (1 blink per second)</th> <th style="width: 20%;">Flashing (1 blink per 2 seconds)</th> <th style="width: 25%;">Visual alarm (1 blink per second)</th> </tr> </thead> <tbody> <tr> <td>Operating time</td> <td align="center">360</td> <td align="center">600</td> <td align="center">600</td> <td align="center">650</td> </tr> </tbody> </table>					Operating mode	Lighting on	Flashing (1 blink per second)	Flashing (1 blink per 2 seconds)	Visual alarm (1 blink per second)	Operating time	360	600	600
Operating mode	Lighting on	Flashing (1 blink per second)	Flashing (1 blink per 2 seconds)	Visual alarm (1 blink per second)										
Operating time	360	600	600	650										
<ul style="list-style-type: none"> ◦ Hassle of periodic charging resolved and Self-discharge rate minimized by applying a separate On/Off switch (Unnecessary to charge for 3 years if not used after fully charged) <p>【Key Functions】</p> <ul style="list-style-type: none"> ◦ Two-way signal communication system type <ul style="list-style-type: none"> – Reciprocal transmission and reception of lighting, flashing, and visual alarm signals between the main body and the emergency button <p>【Precautions for delivery】</p> <ul style="list-style-type: none"> ◦ The main body shall be changed to handle type and delivered. <p>【Product photo】</p> <div style="text-align: center;">  </div> <ul style="list-style-type: none"> ◦ Components: Main body, Charging adapter, Product user manual 														
Remarks	<ul style="list-style-type: none"> – Warranty: 2 durable years of free repair (except for EL Wire) – Submission of certificates and official test results upon delivery (※ Authorized test items: Flame retardant test and 12 other cases) – Patent registered (10-1751433), International PCT application, Korea, USA and Japanese patent registered 													